



MSL/E 2x

Displacement liquid foam proportioning unit for variable flowrate MSL/E 2x type

- with vertical tank in welded carbon steel, capacity 450 lt to 12.000 lt, with manhole, dimensioned according the European Standard 97/23/CE “PED” for working pressure 10 bar, design pressure 12 bar and test pressure 18 bar, with internal Hypalon membrane, with foam compound outside the membrane, with tank pressure indicator, safety valve and metallic plate with technical data of the unit,
- complete of all necessary accessories for the proper operation of the unit,
- level indication with ball valves along the side of the tank, (optionally level indication with flowmeter on the water inlet line to the tank),
- foam proportioning pipe for variable flowrate in welded carbon steel, DN flanged ANSI 150 lbs R.F. (alternative DIN PN 16), with internal Venturi nozzle in stainless steel for flowrate $Q = 200 \div 19.200$ lt/min., with pressure gauges on the proportioning pipe for visualization of the pressure upstream and downstream the Venturi nozzle, with foam compound admixing percentage regulating valve $0 \div 6\%$,
- connecting line and valves between proportioner and tank (water inlet line and foam compound outlet line) in carbon steel with internal part of the valves in stainless steel,
- external protective painting: sandblasting SA 2,5,
 - n.1 epoxy rich primer coat d.f.t.=60 μ ,
 - n.2 final epoxy enamel coats red RAL 3000, d.f.t. =45 μ each, total d.f.t. =150 μ

Optionally:

- internally protected execution for aggressive foam compounds, with internal protective painting: sandblasting SA 3,
 - n.1 epoxy rich primer coat d.f.t.=60 μ ,
 - n.1 final epoxy coat, d.f.t. =40 μ ,
 - total d.f.t. =100 μ
- electric refilling pump mounted on the proportioner and complete with connecting piping



ANSI 150 lbs R.F. flange						
Type	Code nr.	Capacity (lt.)	Dia.Foam Proportioning Pipe and Flange	Flowrate (lt/min)	Weight (Kg)	Dwg. nr.
MSL/E 2x 2K0/6"	0470420610	2000	6"	400 ÷ 3200	1600	04731205
MSL/E 2x 2K5/6"	0470425610	2500	6"	400 ÷ 3200	1800	04731405
MSL/E 2x 3K0/8"	0470430710	3000	8"	800 ÷ 6400	1900	04731602
MSL/E 2x 4K0/8"	0470440710	4000	8"	800 ÷ 6400	2600	04732010
MSL/E 2x 5K0/10"	0470450810	5000	10"	1200 ÷ 9600	3400	04732407
MSL/E 2x 6K0/10"	0470460810	6000	10"	1200 ÷ 9600	3800	04732822
MSL/E 2x 7K0/12"	0470470910	7000	12"	1600 ÷ 12800	4600	04733205
MSL/E 2x 10K0/14"	0470491110	10000	14"	2400 ÷ 19200	6000	04734415
MSL/E 2x 12K0/14"	0470493110	12000	14"	2400 ÷ 19200	7400	04735208
DIN PN 16 flange						
Type	Code nr.	Capacity (lt.)	Dia.Foam Proportioning Pipe and Flange	Flowrate (lt/min)	Weight (Kg)	Dwg. nr.
MSL/E 2x 2K0/6"	0470420620	2000	DN 150	400 ÷ 3200	1600	04731206
MSL/E 2x 2K5/6"	0470425620	2500	DN 150	400 ÷ 3200	1800	04731406
MSL/E 2x 3K0/8"	0470430720	3000	DN 200	800 ÷ 6400	1900	04731601
MSL/E 2x 4K0/8"	0470440720	4000	DN 200	800 ÷ 6400	2600	04732009
MSL/E 2x 5K0/10"	0470450820	5000	DN 250	1200 ÷ 9600	3400	04732406
MSL/E 2x 6K0/10"	0470460820	6000	DN 250	1200 ÷ 9600	3800	04732821
MSL/E 2x 7K0/12"	0470470920	7000	DN 300	1600 ÷ 12800	4600	04733204
MSL/E 2x 10K0/14"	0470491120	10000	DN 350	2400 ÷ 19200	6000	04734414
MSL/E 2x 12K0/14"	0470493120	12000	DN 350	2400 ÷ 19200	7400	04735209