



## MSLI 2x

### Displacement liquid foam proportioning unit for variable flowrate MSLI 2x type

- with vertical tank in welded carbon steel, capacity 450 lt to 12.000 lt, with manhole, dimensioned according the European Standard 97/23/CE “PED” for working pressure 10 bar, design pressure 12 bar and test pressure 18 bar, with internal Hypalon membrane, with internal distribution and stabilizing pipes in stainless steel, with tank pressure indicator, safety valve and metallic plate with technical data of the unit,
- complete of all necessary accessories for the proper operation of the unit,
- level indication with ball valves along the side of the tank, (optionally level indication with flowmeter on the water inlet line to the tank),
- foam proportioning pipe for variable flowrate in welded carbon steel, DN flanged ANSI 150 lbs R.F. (alternative DIN PN 16),
- connecting line and valves between proportioner and tank (water inlet line ) in carbon steel,
- connecting line and valves between tank and proportioner (foam compound outlet line) in stainless steel AISI 304, with internal Venturi nozzle in stainless steel for flowrate  $Q = 200 \div 19.200$  lt/min., with pressure gauges on the proportioning pipe for visualization of the pressure upstream and downstream the Venturi nozzle, with foam compound admixing percentage regulating valve  $0 \div 6\%$ ,
- external protective painting: sandblasting SA 2,5,
  - n.1 epoxy rich primer coat d.f.t.=60 $\mu$ ,
  - n.2 final epoxy enamel coats red RAL 3000, d.f.t. =45 $\mu$  each, total d.f.t. =150 $\mu$
- internally protected execution for aggressive foam compounds, with internal protective painting: sandblasting SA 3,
  - n.1 epoxy rich primer coat d.f.t.=60 $\mu$ ,
  - n.1 final epoxy coat, d.f.t. =40 $\mu$ ,
  - total d.f.t. =100 $\mu$

#### Optionally:

- electric refilling pump mounted on the proportioner and complete with connecting piping



ANSI 150 lbs R.F. flange						
Type	Code nr.	Capacity (lt.)	Dia.Foam Proportioning Pipe and Flange	Flowrate (lt/min)	Weight (Kg)	Dwg. nr.
MSLI 2x 2K0/6"	0473620610	2000	6"	400 ÷ 3200	1600	04711208
MSLI 2x 2K5/6"	0473625610	2500	6"	400 ÷ 3200	1800	04711407
MSLI 2x 3K0/8"	0473630710	3000	8"	800 ÷ 6400	1900	04711607
MSLI 2x 4K0/8"	0473640710	4000	8"	800 ÷ 6400	2600	04712007
MSLI 2x 5K0/10"	0473650810	5000	10"	1200 ÷ 9600	3400	04712407
MSLI 2x 6K0/10"	0473660810	6000	10"	1200 ÷ 9600	3800	04712807
MSLI 2x 7K0/12"	0473670910	7000	12"	1600 ÷ 12800	4600	04713207
MSLI 2x 10K0/14"	0473691110	10000	14"	2400 ÷ 19200	6000	04714407
MSLI 2x 12K0/14"	0473693110	12000	14"	2400 ÷ 19200	7400	04715207
DIN PN 16 flange						
Type	Code nr.	Capacity (lt.)	Dia.Foam Proportioning Pipe and Flange	Flowrate (lt/min)	Weight (Kg)	Dwg. nr.
MSLI 2x 2K0/6"	0473620620	2000	DN 150	400 ÷ 3200	1600	04711207
MSLI 2x 2K5/6"	0473625620	2500	DN 150	400 ÷ 3200	1800	04711408
MSLI 2x 3K0/8"	0473630720	3000	DN 200	800 ÷ 6400	1900	04711608
MSLI 2x 4K0/8"	0473640720	4000	DN 200	800 ÷ 6400	2600	04712008
MSLI 2x 5K0/10"	0473650820	5000	DN 250	1200 ÷ 9600	3400	04712408
MSLI 2x 6K0/10"	0473660820	6000	DN 250	1200 ÷ 9600	3800	04712808
MSLI 2x 7K0/12"	0473670920	7000	DN 300	1600 ÷ 12800	4600	04713208
MSLI 2x 10K0/14"	0473691120	10000	DN 350	2400 ÷ 19200	6000	04714408
MSLI 2x 12K0/14"	0473693120	12000	DN 350	2400 ÷ 19200	7400	04715208