



- △1 - ( 4 x 2.5 mm<sup>2</sup> + 11 x 1.5 mm<sup>2</sup> ) or special cable CMT3 type
- △2 - 4 x n mm<sup>2</sup>, 400 V - 3 Ph 50 Hz, Max current 6A ( breaker 16A )
- △3 - ( 2 x 2.5 mm<sup>2</sup> ) + ( 4 x 1 mm<sup>2</sup> shielded )
- △6 - 13 x 2.5 mm<sup>2</sup> + 2 ( 22 x 1.5 mm<sup>2</sup> ) or alternatively 4 [( 4 x 2.5 mm<sup>2</sup> ) + ( 11 x 1.5 mm<sup>2</sup> )]

0	03.09.2001	Issued		MB	MB	
Rev.	Date		Description	Drawn	Checked	Approved
<b>CACCIALANZA &amp; C. s.p.a.</b> ANTINCENDIO SICUREZZA ANTINQUINAMENTO SEGRATE (MILANO) - ITALY			Title : TYPICAL CONNECTION OF MONITORS TYPE A3-ELE, A4-ELE, A6-ELE, A8-ELE WITH JUNCTION BOX EJBM1 TO STANDARD PANELS EPA11RE+SPAR1	Dwg nr. 46402202		
				Project nr.		
				Sheet nr. 1	of 1	