



- △1 - (4 x 2.5 mm² + 11 x 1.5 mm²) or special cable CMT3 type
- △2 - 4 x n mm², 400 V - 3 Ph 50 Hz, Max current 6A (breaker 16A)
- △3 - (2 x 2.5 mm²) + (4 x 1 mm² shielded)
- △4 - (4 x 1 mm² shielded)
- △5 - 2 x 1.5 mm², 220 V or 400 V - 1 Ph 50 Hz, Max current 2A (breaker 6A)
- △6 - 13 x 2.5 mm² + 2 (22 x 1.5 mm²) or alternatively 4 [(4 x 2.5 mm²) + (11 x 1.5 mm²)]

0	03.09.2001	Issued		MB	MB	
Rev.	Date		Description	Drawn	Checked	Approved
CACCIALANZA & C. s.p.a. ANTINCENDIO SICUREZZA ANTINQUINAMENTO SEGRATE (MILANO) - ITALY			Title : TYPICAL CONNECTION MONITORS TYPE A3-EL, A4-EL, A6-EL, A8-EL WITH J.B. EJBM1 TO PANELS EPA12RE+SPAR1 AND REMOTE PANEL SREPU03	Dwg nr. 46402612 Project nr. Sheet nr. 1 of 1		