



IMPORTANTE :

CACCIALANZA & C. S.p.A. si riserva il diritto di modificare senza preavviso le informazioni contenute su questa scheda con il proposito di apportare miglioramenti alla produzione

IMPORTANT :

CACCIALANZA & C. S.p.A. reserves the right to change or modify without previous notice any data or specification due to changes or modification in order to improve the products presented

PRESSIONE ESERCIZIO : 8 bar (8.2 bar alla flangia d'ingresso)
 OPERATING PRESSURE 8 bar (8.2 bar at inlet flange)

PORTATA : 1800 l/min.
 FLOWRATE

Pos.	Descrizione Description	Q.ty	Material Material	Code Drawing	Note
5	BOCCELLO REGOLABILE TIPO "MS" ADJUSTABLE NOZZLE "MS" TYPE	1			
4	VOLANTINO PER ROTAZIONE HANDWHEEL FOR ROTATION	2			
3	VOLANTINO PER ALZO HANDWHEEL FOR ELEVATION	2			
2	FLANGIA D'INGRESSO INLET FLANGE	1			
1	CORPO MONITORE TIPO AS4-C MONITOR BODY AS4 -C TYPE	1			

Rev.	Date	Description	Drawn	Checked	Approved
0	10.05.2000	Emesso - Issued	MS	MB	
		Client / Project			
		CACCIALANZA & C. <small>s.p.a.</small> ANTINCENDIO SICUREZZA ANTINQUINAMENTO SEGRATE (MILANO) - ITALY			
		Title			
		MONITORE AS4-C CON BOCCELLO TIPO "MS"			
		ASSIEME GENERALE			
		MONITOR AS4-C TYPE WITH WATER ADJUSTABLE NOZZLE "MS" TYPE			
		GENERAL ASSEMBLY			
		Date	Name		
Drawn		10.05.00	M. SPADA		
Checked		10.05.00	M. BARBIERI		
Approved					
Code		Sys.	Size	Scale	Dwg nr.
			A3	1:7.5	52290643
				Rev.	Sheet
				0	1
				of	1
THIS DRAWING IS THE PROPERTY OF CACCIALANZA & C. S.p.A. AND IS NOT TO BE REPRODUCED OR USED TO FURNISH ANY INFORMATION FOR MAKING OF DRAWINGS OR APPARATUS EXCEPT WHERE PROVIDED FOR BY AGREEMENT WITH SAID COMPANY					